FILTER DRIER FOR TRUCK REFRIGERATION

DRIER SERIES

Dry All®
Full Range of HVAC&R Line Products

FILTER DRIER FOR TRUCK REFRIGERATION			
Sr. No	Connection Size	Type	Dry All Model No.
1	3/8" x 3/8 ORFS	Solid Core	DCHLD-163R
2	1/2" x 1/2" ORFS	Solid Core	DCHLD-164R
3	3/8" x 3/8" ORFS	Solid Core	DCHLD-163RL
4	5/8" x 1/2" ORFS	Solid Core	DCH-415-4R
5	1/2" x 1/2 Flare	Solid Core	DCH-414F
6	5/8" x 1/2	Solid Core	DCH-415-4Flare
7	1/2 x 1/2" Flare-Groove	Solid Core	DCH-305R
8	1/2" x 1/2" Flare-Groove	Solid Core	DCH-414ORF
9	1/2" x 1/2" Flare-Groove	Solid Core	DCHLD-164ORF
10	3/8" x 3/8" ORFS	Solid Core	DCH-303R
11	1/2" x 1/2" ORFS	Solid Core	DCH-304R
12	1/4" x 1/4" ORFS	Solid Core	DCHLD-162R
13	3/8" x 3/8" Flare	Solid Core	DCH-303F
14	3/8" x 3/8" Flare	Solid Core	DCH-163F
15	1/2" x 1/2" Flare	Solid Care	DCH-164F
16	3/8" x 3/8" Flare	Solid Care	DCH-083F
17	1/2" x 1/2" Flare	Solid Core	DCH-304F
18	5/8" x 5/8" Flare	Solid Core	DCH-305F

Connection Nomenclature	
F	Flare Connection
S	Solder Connection
R	Rotolock Connection
ORN	'O' Ring
RL	Rotolock 'L' Type
ORF	'O' Ring Connection

1) Internal Assembly - Solid Core Type
2) Maximum Working Pressure - 45 bar (653 psig)
3) Temperature range -40°C to 70°C
4) SAE, ORFS & 'O'Ring Type Connection are in Steel, Nickel Plated
5) ODF Type Connection is in Steel & Nickel Plated
6) *Mark Connection Steel Plated